

**LIST OF CURRENT CLAIMS**

1. (Currently Amended) Fibre reinforced film, ~~characterized in that it is composed of comprising~~ a basalt fibre layer (2) ~~which is provided having~~ on at least one side ~~with thereof~~ a layer of thermoplastic material (3).

2. (Currently Amended) Fibre reinforced film according to claim 1, ~~characterized in that wherein~~ the basalt fibre layer (2) ~~is provided includes~~ both sides ~~with~~ a layer of thermoplastic material (3), ~~which layers adhere each adhering to each the~~ other through the openings between the basalt fibres, such that a matrix of thermoplastic material is created which comprises the basalt fibres.

3. (Currently Amended) Fibre reinforced film according to claim 1 ~~or 2~~, ~~characterized in that it is provided with~~ including perforations (5) in the film.

4. (Currently Amended) Fibre reinforced film according to claim 1 ~~or 2~~, ~~characterized in that it is provided with~~ including a membrane (6) on at least one side of the film.

5. (Currently Amended) Fibre reinforced film according to claim 1 ~~or 2~~, ~~characterized in that it is provided with~~ including a bonding layer (7) on at least one side of the film.

[[8]] 6. (Currently Amended) Fibre reinforced film according to claim 1 ~~or 2~~, ~~characterized in that it is provided with~~ including a membrane (6) on one side of the film and ~~with~~ a bonding layer (7) on the other side of the film.

7. (Currently Amended) Fiber reinforced film according to claim 4, ~~characterized in that~~ including a barrier layer between the layer of thermoplastic material (3) and the membrane (6) ~~is provided a barrier layer (9)~~.

8. (Currently Amended) Fibre reinforced film according to claim 7, ~~characterized in that~~ including a bonding layer between the layer of thermoplastic material (3) and the barrier layer (9) ~~is provided a bonding layer (8).~~

9. (Currently Amended) Fibre reinforced film according to claim 7, ~~characterized in that~~ including a bonding layer between the barrier layer (9) and the membrane (6) ~~is provided a bonding layer (10).~~

10. (Currently Amended) Fibre reinforced film according to claim 5 ~~or 6~~, characterized ~~in that~~ wherein the bonding layer (7-9-10) mainly consists of ~~for example~~ comprises bonding material selected from the group consisting of ethylene vinyl acetate, ethylene acrylic acid, and co-polyester or co-polyamide.

11. (Currently Amended) Fibre reinforced film according to claim 4, ~~6, 7 or 9~~, characterized ~~in that~~ wherein the membrane (6) mainly consists of comprises material selected from the group consisting of polyester viscose, polyester cellulose ~~or and~~ paper.

12. (Currently Amended) Fibre reinforced film according to claim 1 ~~or 2~~, characterized ~~in that~~ wherein the layer of thermoplastic material (3) or the thermoplastic matrix is coloured.

13. (Currently Amended) Fibre reinforced film according to claim 1 ~~or 2~~, characterized ~~in that~~ wherein the basalt fibre layer (2) is made as comprises a basalt fibre mat (4).

14. (Currently Amended) Method for manufacturing a basalt fibre reinforced film according to one of several of the preceding claims, characterized in that comprising the steps:

providing a basalt fiber layer;

~~(2) is supplied and in that~~ providing a layer of thermoplastic material on at least

on one side of the basalt fibre layer;

~~(2) is provided a layer of thermoplastic material on (3) after which then pressing and cooling the layer of thermoplastic material (3) is pressed on and cooled.~~

15. (Currently Amended) Method according to claim 14, ~~characterized in that~~ wherein, after a layer of thermoplastic material (3) has been provided on one side, and after it has been pressed on and cooled, the basalt fibre layer (2) with the layer of thermoplastic material (3) ~~provided on it~~ is turned, so that the provided layer of thermoplastic material (3) is ~~situated~~ disposed at or near the bottom, ~~or practically at the bottom~~, after which a second layer of thermoplastic material (3) is provided on the upward directed side of the basalt fibre layer (2), after which ~~this~~ the second layer of thermoplastic material is pressed on and cooled.

16. (Currently Amended) Method according to claim 14, ~~characterized in that~~ wherein, together with a layer of thermoplastic material (3) provided by means of extrusion, a membrane (6) is applied by means of co-lamination.

17. (Currently Amended) Method according to claim 14, ~~characterized in that~~ wherein, together with a layer of thermoplastic material (3) being applied, a bonding layer (7) is applied.

18. (Currently Amended) Method according to claim 14, ~~15 or 16, characterized in that~~ wherein after one or several layers of thermoplastic material (3) have been applied, and after they have been pressed on and cooled, and ~~possibly optionally~~ either or both a membrane (6) ~~and/or~~ and a bonding layer (7) has been provided, the film (1) is perforated.

19. (Currently Amended) Method according to ~~any one of claims 14 to 18~~ claim 14, including applying a layer of thermoplastic material (3) ~~is applied~~ by means of extrusion or co-extrusion.